








LOAD FEEDER, FUSELESS DIRECT START, AC 400V, SIZE S2, 40...50A, DC 400V, 50/60HZ, SCREW CONNECTION FOR DIN RAIL MOUNTING, IQ = 50KA 1NO+1NC (CIRCUIT BREAKER)

Фирменное название продукта

SIRIUS

Сертификаты/допуски к эксплуатации

General Product Approval	For use in hazardous locations	Declaration of Conformity	Shipping Approval		
 <p>UL</p>	 <p>EAC</p>	 <p>ATEX</p>	 <p>IECEX</p>	 <p>EG-Konf.</p>	 <p>LRS</p>

Shipping Approval	other
 <p>RMRS</p>	<p>Environmental Confirmations</p> <p>Confirmation</p>

Дополнительная информация

Information- and Downloadcenter (каталоги, брошюры,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Каталог и система обработки заказов)

<https://mall.industry.siemens.com/mall/ru/ru/Catalog/product?mlfb=3RA1135-6HA36-0AR6>

Онлайн-генератор Cax

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA1135-6HA36-0AR6>

Service&Support (руководства, инструкции по эксплуатации, сертификаты, указания, FAQ,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RA1135-6HA36-0AR6>

Банк изображений (фотографии продуктов, двухмерные размерные чертежи, трехмерные модели, схемы приборов,

макросы EPLAN, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA1135-6HA36-0AR6&lang=en

последнее изменение:

10.07.2017