

MLFB-Ordering data

6FX2001-2PD60



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Electrical data	Mechanical data
-----------------	-----------------

<table style="width:100%; border-collapse: collapse;"> <tr> <td style="width:30%;">Operating voltage Up</td> <td>DC 5 V ± 10 %</td> </tr> <tr> <td>Max. power consumption without load</td> <td>150 mA</td> </tr> <tr> <td>Signal level</td> <td>TTL (RS 422)</td> </tr> <tr> <td>Resolution</td> <td>3600 S/R</td> </tr> <tr> <td>Accuracy</td> <td>18 rad</td> </tr> <tr> <td>Sampling frequency, max.</td> <td>300 kHz</td> </tr> <tr> <td>Switching time (10 ... 90 %)</td> <td><= 50 ns</td> </tr> <tr> <td></td> <td>Rise / fall time t+/t- <=</td> </tr> <tr> <td>Phase relation signal A to B</td> <td>90°</td> </tr> <tr> <td>Edge clearance at 300 kHz</td> <td>0.45 µs</td> </tr> <tr> <td>LED failure monitoring</td> <td>High impedance driver</td> </tr> </table>	Operating voltage Up	DC 5 V ± 10 %	Max. power consumption without load	150 mA	Signal level	TTL (RS 422)	Resolution	3600 S/R	Accuracy	18 rad	Sampling frequency, max.	300 kHz	Switching time (10 ... 90 %)	<= 50 ns		Rise / fall time t+/t- <=	Phase relation signal A to B	90°	Edge clearance at 300 kHz	0.45 µs	LED failure monitoring	High impedance driver	<table style="width:100%; border-collapse: collapse;"> <tr> <td style="width:30%;">Shaft diameter</td> <td>10 mm</td> </tr> <tr> <td>Shaft length</td> <td>20 mm</td> </tr> <tr> <td>Angular acceleration, max.</td> <td>100000 rad/s²</td> </tr> <tr> <td>Moment of inertia of rotor</td> <td>0.00000145 kgm²</td> </tr> <tr> <td>Vibration (55...2000 Hz), max.</td> <td>300 m/s²</td> </tr> <tr> <td>Friction torque (at 20°C), max.</td> <td>0.01 Nm</td> </tr> <tr> <td>Starting torque (at 20°C), max.</td> <td>0.01 Nm</td> </tr> <tr> <td>Net weight</td> <td>0.3 kg</td> </tr> <tr> <td colspan="2">Speed max.</td> </tr> <tr> <td>Max. permissible speed (elec.)</td> <td>5000 rpm</td> </tr> <tr> <td>Max. permissible speed (mech.)</td> <td>12000 rpm</td> </tr> </table>	Shaft diameter	10 mm	Shaft length	20 mm	Angular acceleration, max.	100000 rad/s ²	Moment of inertia of rotor	0.00000145 kgm ²	Vibration (55...2000 Hz), max.	300 m/s ²	Friction torque (at 20°C), max.	0.01 Nm	Starting torque (at 20°C), max.	0.01 Nm	Net weight	0.3 kg	Speed max.		Max. permissible speed (elec.)	5000 rpm	Max. permissible speed (mech.)	12000 rpm
Operating voltage Up	DC 5 V ± 10 %																																												
Max. power consumption without load	150 mA																																												
Signal level	TTL (RS 422)																																												
Resolution	3600 S/R																																												
Accuracy	18 rad																																												
Sampling frequency, max.	300 kHz																																												
Switching time (10 ... 90 %)	<= 50 ns																																												
	Rise / fall time t+/t- <=																																												
Phase relation signal A to B	90°																																												
Edge clearance at 300 kHz	0.45 µs																																												
LED failure monitoring	High impedance driver																																												
Shaft diameter	10 mm																																												
Shaft length	20 mm																																												
Angular acceleration, max.	100000 rad/s ²																																												
Moment of inertia of rotor	0.00000145 kgm ²																																												
Vibration (55...2000 Hz), max.	300 m/s ²																																												
Friction torque (at 20°C), max.	0.01 Nm																																												
Starting torque (at 20°C), max.	0.01 Nm																																												
Net weight	0.3 kg																																												
Speed max.																																													
Max. permissible speed (elec.)	5000 rpm																																												
Max. permissible speed (mech.)	12000 rpm																																												

Cable length

To the downstream electronics, max. 100 m

Ambient temperature Operation

Fixed installation of flange outlet or cable

- At Up = 5V ± 10% -40 ... 100 °C

Flexible cable

- At Up = 5V ± 10% -10 ... 100 °C

Standards

Compliance with standards	CE, cULus
EMC class filter	Tested according to the EMC guidelines 89/336/EEC and the rules of the EMC guidelines (generic standards)

Load capacity

n = 6000 rpm	
- Axial	10 N
- Radial at shaft end	20 N
n > 6000 rpm	
- Axial	40 N
- Radial at shaft end	60 N

Shock, max.

2 ms	2000 m/s ²
6 ms	1000 m/s ²

Degree of protection

Without shaft input	IP67
With shaft input	IP64