



CorePro LEDspot MV

CorePro LEDspotMV 5-50W GU10 830 60D

CorePro LEDspots are a perfect fit for spot lighting . They are compatible with most existing fixtures with a GU10 or E14 holder and are designed as a retrofit replacement for halogen or incandescent spots. LEDlamps deliver huge energy savings and minimize maintenance cost.

Product data

General Information	
Cap-Base	GU10 [GU10]
Nominal Lifetime (Nom)	15000 h
Switching Cycle	50000X
Technical Type	5-50W
Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	60 °
Luminous Flux (Nom)	385 lm
Luminous Flux (Rated) (Nom)	385 lm
Luminous Intensity (Nom)	450 cd
Color Designation	White (WH)
Rated Beam Angle	60 °
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	72.00 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux In 90° Cone (Rated)	360 lm

Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	5 W
Lamp Current (Nom)	40 mA
Wattage Equivalent	50 W
Starting Time (Nom)	0.5 s
Warm Up Time To 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.5
Voltage (Nom)	220-240 V

Temperature	
T-Case Maximum (Nom)	85 °C

Controls and Dimming	
Dimmable	No

Approval and Application	
Energy Saving Product	Yes
Suitable For Accent Lighting	Yes
Energy Efficiency Label (EEL)	A+
Energy Consumption kWh/1000 h	5 kWh


CorePro LEDspot MV

Product Data

Full product code	871869656340300
Order product name	CorePro LEDspotMV 5-50W GU10 830 60D
EAN/UPC - Product	8718696563403
Order code	929001220702
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	10
Material Nr. (12NC)	929001220702
Net Weight (Piece)	0.038 kg

Dimensional drawing



GU10 230V 5W-50W 60D 3000K ND

Product	D	C
CorePro LEDspotMV 5-50W GU10 830 60D	50 mm	54 mm

Photometric data

